



# Chicago Pneumatic



## SIZE MATTERS New Ultra Compact Tool

*#CPsizeMatters*



- ✓ 20% lighter than the previous generation
- ✓ Improved power:  
460 ft.lbs / 625 Nm  
of max. torque in reverse

### CP7732C

**1/2" Stubby Impact Wrench**



**Vehicle  
Service**Tools

**People. Passion. Performance.**

2.2 lbs. - 1.0 kg  
20%  
LIGHTER  
Ultra Lightweight

# CP7732C

## 1/2" Stubby Impact Wrench



4-1/4 IN. - 108 MM ONLY

### POWERFUL

460 ft.lbs - 625 Nm of maximum torque in reverse

### HIGH DURABILITY & ROBUST

- Jumbo hammer mechanism
- Steel motor
- Aluminum clutch housing

### COMFORT & LIGHTWEIGHT

- Composite housing
- Curved handle with Thermo-Plastic Rubber injected housing, for a durable and comfortable grip

### CONVENIENT


Socket retainer ring

### EASY OPERATION

- S2S "Side-to-side": 1 handed Forward - Reverse operation
- New power setting system: 1 handed-operation behind the trigger
  - 2 positions in reverse: maximum and low torque
  - 2 positions in forward: maximum and low torque

### GREAT CONTROL

Full teasing trigger



### DIMENSIONS

| A   |     | B   |     | C   |    |
|-----|-----|-----|-----|-----|----|
| in. | mm  | in. | mm  | in. | mm |
| 4.3 | 108 | 7.5 | 190 | 2.6 | 65 |

| Model   | Part number  | Anvil | Speed | Working torque |          | Max torque |     | Weight |     | Length |     | Air cons. average |     | Air cons. @ load |      | Sound level | Vibration            | Inner hose diameter |    | Air inlet |
|---------|--------------|-------|-------|----------------|----------|------------|-----|--------|-----|--------|-----|-------------------|-----|------------------|------|-------------|----------------------|---------------------|----|-----------|
|         |              | inch  | RPM   | ft-lbs.        | Nm       | ft-lbs.    | Nm  | lbs    | kg  | inch   | mm  | cfm               | l/s | cfm              | l/s  | dBA         | m/s <sup>2</sup> (k) | in                  | mm | in        |
| CP7732C | 894 107 7321 | 1/2   | 9,410 | 52 - 285       | 70 - 387 | 460        | 625 | 2.2    | 1.0 | 4 1/4  | 108 | 5.5               | 2.6 | 22               | 10.2 | 95.5        | 10.8 (1.42)          | 3/8                 | 10 | 1/4       |

All models: Hose int. 3/8" (10 mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check tool documentation.

### STANDARD OR MAGNETIC 1/2" SOCKET SETS

| Model   | Part #       | Type   | Pc | Set content                                                                     |
|---------|--------------|--------|----|---------------------------------------------------------------------------------|
| SS4114  | 894 016 4458 | Metric | 14 | 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 26 & 27 mm                      |
| SS4013  | 894 016 4465 | SAE    | 13 | 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16, 1, 1-1/16, 1-1/8, & 1-1/4" |
| SS4112G | 894 016 4462 | Metric | 12 | 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20 & 21 mm                              |
| SS4011G | 894 016 4469 | SAE    | 11 | 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16 & 1"                   |

### 2 STAGE COMPOSITE 1/4" FRL

| Part #       | Type | Max. Flow Rate |       |
|--------------|------|----------------|-------|
|              |      | cfm            | l/sec |
| 894 017 1944 | NPT  | 74             | 34    |
| 894 017 1927 | BSP  | 74             | 34    |

### TUNE-UP KIT

| Model   | Tune-up Kit  |
|---------|--------------|
| CP7732C | 894 017 3823 |

Chicago Pneumatic also offers a large range of air tools, accessories, and workshop equipment to optimize your air tools durability and performance: Check [www.cp.com](http://www.cp.com) website for more information.



[www.cp.com](http://www.cp.com)